TUP SEURE 1 Approved For Release 2002/05/02 : CIA-RDP78B04767A060300050020-0

TECHNICAL BACKGROUND AND RESULTS TO DATE

The Bi-Color Technique

- photography. The only difference between bi-color and normal acquisition is the use of a green filter on one camera. Normally, we use red filters on both forward and aft looking cameras. In the case of bi-color, we use a green filter on one camera and a red filter on the other to provide for spectral discrimination. The green filter need not be used all the time but only on those passes desired, due to the in-flight changeable filter mechanism on the KH-4B camera. Conceptually, then, this technique works as follows:
 - a. To provide bi-color, the red and green filters are used. The normal high resolution black and white film, Type 3404, is employed. Even in the bi-color mode this produced typical high resolution stereo coverage.
 - b. Dupe positives are made in the normal fashion.

 And the photointerpreters can do their normal job.
 - c. Since spectral separation is provided by the red and green filters, color can be seen if the two records are projected back through the red and green filters, and then superimposed.

 Although this is not complete color (the blue record is missing), highly realistic color can be produced with some manipulation.

25X1A

Approved For Release 2002/05/02 CARDET BB04767A000300050020-0

Technical Background and Results To Date

The records can also be evaluated, as black and whites for spectral differences. This may give clues as to the general composition of objects. The green record may also show objects which the normal red record does not show. The use of the bicolor records, then, is optional depending on the information desired. In summary, they can be used for any task from normal photointerpretation, to the production of "psuedo" color prints.

Results to Date

X1A and sa	atellite ()	has been tested	
	atellite (Mission	11102) systems.	The 1102 test confined itself to
		the major num	
25X1A	and its opera	tional implementa	tion. The highlights were as follows:
			were taken with the red

NPIC evaluated the film (in particular, the green record) to assess its photointerpretation use and quality. We were particularly interested in assessing the impact of the bi-color take on the ability of the photointerpreter to do his normal job.

The results of the NPIC evaluation were reported in

25X1A

25X1A

Approved For Release 2002/05/02 : CIA-RDP78B04767A000300050020-0 TOP SECRET

Approved For Release 2002/05/02 CSF-RRIZ78B0476ZA000300050020-0

SUBJECT: Technical Background and Results To Date

"The general conclusion of the photo-interpreters is that the majority of the requirements levied for the KH-4B system could be answered with photography generated in the bi-color mode because when used in stereo, the two records complement each other. In addition, the overall information content of the photography exposed through the green filter is comparable to an average KH-4A mission."

25X1A

c. We also had our contractor produce several color prints

This demonstrated that approximately natural color could be produced. This also demonstrated the problem of registration of the bi-color due to the geometry of the pan cameras. It was determined that orthoprinting was necessary to enable making bi-color prints. To avoid this problem, OSP provided NPIC with an Automatic Registration Electronic Stereoscope (ARES) which allows the photointerpreter to view his normal dupes in color. This equipment rectifies the images and allows NPIC to use the bi-color mode without orthoprinting. Other bi-color equipment is to be provided NPIC in the near future.

25X1A

Approved For Release 2002/05/02 : CIA-RDP 38802 67 A000300050020-0

SUBJECT: Technical Background and Results To Date

Conclusions/Recommendations

- 3. The NRO Ad Hoc Committee* conclusions and recommendations relative to bi-color are summarized as follows:
 - a. Bi-color can be successfully implemented on the KH-4B system.
 - b. Insofar as the PI is concerned, there is no loss in ground resolution through the red filter. The loss in the green filter is the equivalent of KH-4B to KH-4A photography. The PI can do his normal job with bi-color acquisition.
 - c. The intelligence value of bi-color has not been proven.

 To assess its use, it must be flown against specific intelligence requirements involving operational targets.
 - d. The NRO Ad Hoc Committee has concluded

 that there is no technical or photointerpreter reason why bi-color

 cannot be flown operationally if COMIREX so desires. The NRO

 Committee has concluded that the operational usefulness of bi-color

 can only be assessed by flying it against specific intelligence questions.

25X1A

*NRO Ad Hoc Committee on KH-4B Photographic Experiments

Next 5 Page(s) In Document Exempt